



BOARD'S DRILL SCHEDULE

DRILL SYMBOL	DRILL SIZE	COUNT	PLATED	Tolerance	COMMENT
○	.05	100	YES	---	
⊞	.12	4	YES	---	

Layer Order  
2-Layer Flex PCB



Film 1 - Component Side  
Film 2 - Bottom

Board Characteristics

0. Materials can be changed as required by application
1. All dimensions in mm, unless specified
2. Minimum trace width/gap: 0.205mm/0.3mm
3. 0.5 Oz Copper on all layers
4. Silkscreen on Component Side.

7. Place Stiffener on Top (Component) side of Flex PCB.
8. Stiffener size as per flex PCB

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCES ARE: FRACTIONS    DECIMALS    ANGLES :XX :XXX DO NOT SCALE DRAWING	CONTRACT NO.		UNIVERSITY OF CHICAGO ELECTRONICS DEVELOPMENT GROUP		
	APPROVALS	DATE	TITLE DAMIC - Ext Flex PCB 1.5m Specification Drawing		
TREATMENT	DRAWN				
FINISH	CHECKED M. Bogdan	9/30/2021	SIZE	FSCM NO.	DWG. NO.
	ISSUED M. Bogdan	9/30/2021	B		3010
					REV. A